

# Navojni spojevi sa reznim prstenovima za pneumatske kočione sisteme

● Pocičani čelik, žuto kromatiziran prema DIN standardu.



## Tipovi spojeva Utični

## Čeoni spoj

## Kompletni navojni spojevi



ORSY



ORSY



ORSY

## Ravni jednostrani navojni spojevi

za cijev-Ø	M	max. radni pritisak bar	Tip spoja	Art.-Nr.
8	12 x 1,5	20	Utični	<b>0884 020 812</b>
12	16 x 1,5			<b>0884 021 216</b>

Pak/kom: 5

## Ravni jednostrani navojni spojevi

za cijev-Ø	M	max. radni pritisak bar	Tip spoja	Art.-Nr.
6	16 x 1,5	20	Utični	<b>0884 010 616</b>
6	22 x 1,5			<b>0884 010 622</b>
8	16 x 1,5			<b>0884 010 816</b>
8	22 x 1,5			<b>0884 010 822</b>
10	22 x 1,5			<b>0884 011 022</b>
12	22 x 1,5			<b>0884 011 222</b>
15	22 x 1,5		Čeoni	<b>0884 011 522</b>

Pak/kom: 5

## Ravni dvostrani navojni spojevi

za cijev-Ø	max. radni pritisak bar	Tip spoja	Art.-Nr.
6/6	250	Utični	<b>0884 030 601 *</b>
6/6			<b>0884 030 602 **</b>
8/8			<b>0884 030 801</b>
8/6			<b>0884 030 806</b>
10/10			<b>0884 031 001</b>
12/12			<b>0884 031 201</b>
12/10		<b>0884 031 210</b>	
15/15	20	Čeoni	<b>0884 031 501</b>

Pak/kom: 5

\* SW 17

\*\* SW 12



ORSY



ORSY



ORSY

## Ravni pregradni navojni spojevi

za cijev-Ø	M	max. radni pritisak bar	Tip spoja	Art.-Nr.
12	16 x 1,5	20	Utični	<b>0884 081 216</b>
12	22 x 1,5			<b>0884 081 222</b>
15	22 x 1,5		Čeoni	<b>0884 081 522</b>

Pak/kom: 5

## Ugaoni dvostrani navojni spojevi

za cijev-Ø	max. radni pritisak bar	Tip spoja	Art.-Nr.
6/6	250	Utični	<b>0884 050 601</b>
8/8			<b>0884 050 801</b>
10/10			<b>0884 051 001</b>
12/12			<b>0884 051 201</b>

Pak/kom: 5

## Ugaoni jednostrani navojni spojevi

za cijev-Ø	M	max. radni pritisak bar	Tip spoja	Art.-Nr.
10	16 x 1,5	20	Utični	<b>0884 041 016</b>
12	16 x 1,5			<b>0884 041 216</b>
12	22 x 1,5			<b>0884 041 222</b>
15	22 x 1,5			<b>0884 041 522</b>
			Čeoni	

Pak/kom: 5