



Cjevaste kabl-stopice

sa plasti-nom ~ahurom

- Za provodnike od 0,5 do 95 mm².
- Nekoliko du`ina ~ahura po boji.
- Unutra{nja cjevna spojnica toplo-otporna do 110°C.
- Cijev: Cu, galvanski kalajisana.
- Bez halogena.

Popr. presjek mm ²	Boja identifikacije		Dimenzije mm						Art.-Nr. A	Pak/kom A	Art.-Nr. B	Pak/kom B
	A	B	l ₁	l ₂	d ₁	s ₁	d ₂	s ₂				
0,14	sme a		10,4	6,0	0,7	0,12	1,6	0,20	1000			
			12,4	8,0								
0,25	ljubi-asta		10,4	6,0	0,8		1,8		1000			
			12,4	8,0								
0,34	`uta		10,4	6,0	1,1		2,3		1000			
			12,4	8,0								
0,5	bijela	narand`.	12,0	6,0	1,0		2,6		500/1000	0557 000 501	1000	
			14,0	8,0					100/500/1000	0557 000 50		
			16,0	10,0					500	0557 000 503	500	
0,75	plava	bijela	12,4	6,0	1,2		2,8		1000	0557 000 751	1000	
			14,6	8,0						0557 000 75		
	16,4		10,0						0557 000 753			
	18,4		12,0						0557 000 754	500		
1,0	crvena	`uta	12,0	6,0	1,4		3,0		500/1000	0557 001 001	1000	
			14,0	8,0					100/500/1000	0557 001 00		
	16,4		10,0						0557 001 003			
	18,4		12,0						0557 001 004	500		
1,5	crna	crvena	14,0	8,0	1,7		3,5		100/500/1000	0557 001 50	1000	
			16,0	10,0					500/1000	0557 001 503		
			24,0	18,0					500	0557 001 504	500	
2,5	siva	plava	14,0	8,0	2,2		4,0		1000	0557 300 251	100/500/1000	
			18,0	12,0						0557 300 252	500/1000	
	24,0		18,0	500					0557 100 251	500	0557 300 253	500
4,0	narand`.	siva	17,8	10,0	2,8		4,4			0557 300 401	100/1000	
			19,5	12,0					1000	0557 300 402		
			25,5	18,0				100	0557 100 401	0557 300 403	100	
6,0	zelena	crna	20,0	12,0	3,5		6,3	0,40	500	0557 100 60	0557 006 00	500
			26,0	18,0					100	0557 100 61	0557 006 004	100
10,0	sme a	slonova-a	21,5	12,0	4,5		7,6		500	0557 100 100	0557 010 00	500
			27,5	18,0						0557 100 110	0557 010 004	