



Cijevne kabl-stopice

komercijalne

(slično prema DIN)

- Materijal: cijev od elektrolitičkog bakra prema EN 13600.
- Površina: galvanski kalajisana.
- Temperaturna postojanost do +125°C.
- Izvedba: sa otvorom za vizuelnu kontrolu.

Poprečni presjek mm ²	Otvor prirubnice	Dimenzije mm					Art.-Nr.	Pak/kom
		d ₁	e	b	a	Ø d ₂		
6,0	M 5	3,5	20,5	10,0	9,5	5,3	0967 206 5	100
	M 6		20,5	12,0		6,4	0967 206 6	
	M 8		23,0	15,0		8,4	0967 206 8	
	M 10		25,0	17,0		10,5	0967 206 10	
10,0	M 5	4,5	22,5	12,0	10,5	5,3	0967 210 5	100
	M 6		22,5	12,0		6,4	0967 210 6	
	M 8		25,0	15,0		8,4	0967 210 8	
	M 10		27,0	17,0		10,5	0967 210 10	
16,0	M 5	5,5	26,0	12,0	13,0	5,3	0967 216 5	100
	M 6		27,0	12,0		6,4	0967 216 6	
	M 8		29,0	15,0		8,4	0967 216 8	
	M 10		31,0	17,0		10,5	0967 216 10	
	M 12		32,5	19,0		13,2	0967 216 12	
25,0	M 5	7,0	30,0	14,0	15,0	5,3	0967 225 5	100
	M 6		30,0	14,0		6,4	0967 225 6	
	M 8		32,5	16,0		8,4	0967 225 8	
	M 10		34,5	18,0		10,5	0967 225 10	
	M 12		35,5	19,0		13,2	0967 225 12	
35,0	M 6	8,5	32,5	17,0	17,0	6,4	0967 235 6	50
	M 8		35,0	17,0		8,4	0967 235 8	
	M 10		37,0	19,0		10,5	0967 235 10	
	M 12		38,0	21,0		13,2	0967 235 12	
	M 16		41,0	26,0		17,0	0967 235 16	
50,0	M 6	10,0	37,0	20,0	19,0	6,4	0967 250 6	50
	M 8		37,0	20,0		8,4	0967 250 8	
	M 10		39,0	20,0		10,5	0967 250 10	
	M 12		40,0	23,0		13,2	0967 250 12	
	M 16		43,0	28,0		17,0	0967 250 16	
70,0	M 8	12,0	43,0	23,0	21,0	8,4	0967 270 8	25
	M 10		45,0	23,0		10,5	0967 270 10	
	M 12		46,0	23,0		13,2	0967 270 12	
	M 16		49,0	28,0		17,0	0967 270 16	
95,0	M 8	13,5	48,0	26,0	25,0	8,4	0967 295 8	25
	M 10		48,0	26,0		10,5	0967 295 10	
	M 12		49,0	26,0		13,2	0967 295 12	
	M 16		52,0	28,0		17,0	0967 295 16	
120,0	M 10	15,0	51,0	28,0	26,0	10,5	0967 212 010	25
	M 12		51,0	28,0		13,2	0967 212 012	
	M 16		53,0	30,0		17,0	0967 212 016	
	M 20		59,0	36,0		21,0	0967 212 020	
150,0	M 10	16,5	58,0	31,0	30,0	10,5	0967 215 010	25
	M 12		58,0	31,0		13,2	0967 215 012	
	M 16		58,0	31,0		17,0	0967 215 016	
	M 20		64,0	36,0		21,0	0967 215 020	
185,0	M 10	19,4	65,0	36,0	30,0	10,5	0967 218 510	25
	M 12		65,0	36,0		13,2	0967 218 512	
	M 16		65,0	36,0		17,0	0967 218 516	
	M 20		69,0	39,0		21,0	0967 218 520	
240,0	M 12	21,2	72,0	39,0	35,0	13,2	0967 224 012	25
	M 16		72,0	39,0		17,0	0967 224 016	
	M 20		72,0	39,0		21,0	0967 224 020	