
















Vanjski navoj	Unutrašnji navoj	Vrsta tiplje	Izgled (slika) tiplje	Veličina navoja tj. Ø-navoja tiplje u mm	Dostupne izvedbe				
					Čelik pocinčani	Toplo-cinčani čelik	Nehrđajući čelik A2	Tipla ispod ugradben. elementa	Moguće trenutno opterećenje
		Tipla za izolacione materijale sa ekspanzionim ekserom W-DSD			Ø 10				
		Ekser za izolacione materij. W-IN		Ø 8					
		Ekser za izolacione materijale i tanjir za izolac. materij. W-MID		Ø 8	●		●		
		Najlon tiplja		Ø 4 - 20					
		ZEBRA Shark W-ZX®		Ø 5 - 14					
		ZEBRA® Shark-tipla		Ø 5 - 14					
●		ZEBRA® udarna (ekser) tiplja		Ø 5 - 10	●		●		
		Fix-čahura		Ø 6 - 8	●				
		Udarna zakovica		Ø 4,8 - 6,4			●		
	●	Mesing tiplja		M4 - M16					
		Tipla za zvučnu zaštitu W-SSD		Ø 10 - 18					
		Amo®-Max		Ø 40					
		Amo®-light-vijak		Ø 10	●				

		DIVA® 1 Premium			●				
		DIGA® CS-1 visoko- učinkoviti gasni uređaj			●				