

ZEBRA® 3-K odvijači

Fleksibilna 3-komponentna ručka osigurava perfektu ergonomiju, prenos snage i ugodan rad.



Odvijač Ravni

Oštrica: šestougaona prolazna, mat kromirana; prihvat za ključ mat niklovan, poboljšana udarna žilavost. Velika udarna kapa. Prihvat: DIN 5264-A, ISO 2380 sa Black-Point vrhom.

* bez udarne kape i prihvata za ključ

				Art.-Nr.	
a mm	A mm	B/C mm	inch		
0,6 x 3,5	80	83/27	1/8 x 3 1/16"	0613 200 035*	1
0,8 x 4,5	90	96/31	3/16 x 3 3/5"	0613 200 045	
1,0 x 5,5	100	96/31	7/32 x 4"	0613 200 055	
1,2 x 7,0	125	106/35	9/32 x 5"	0613 200 07	
1,6 x 9,0	150	114/38	11/32 x 6"	0613 200 09	
1,6 x 10,0	175	114/38	3/8 x 7"	0613 200 10	
2,0 x 12,0	200	114/38	1/2 x 8"	0613 200 12	



Odvijač Krstasti (PH)

Oštrica: šestougaona prolazna, mat kromirana; prihvat za ključ mat niklovan, poboljšana udarna žilavost. Würth sistem označavanja u bojama. Velika udarna kapa. Prihvat: DIN 5260-PH, ISO 8764-PH sa Black-Point vrhom.

				Art.-Nr.	
	A mm	B/C mm	inch		
PH1	80	96/31	3 1/8"	0613 201 1	1
PH2	100	106/35	4"	0613 201 2	
PH3	150	114/38	6"	0613 201 3	



Setovi odvijača za automehaničarske radionice i metaloprerađu

Set			Art.-Nr.	
5-dijelni	1,0x5,5 / 1,2x7,0 / 1,6x9,0 mm	PH1 PH2	0613 901 5	1
3-dijelni	1,0x5,5 / 1,2x7,0 mm	PH2	0613 901 3	