



Slijepa zakovica Standard

Zaobljena glava sa ravnim dosjedom DIN 7337

Čahura zakovice: AlMg 2,5
Trn zakovice: čelik pocinčani, plavo pasivirani

Standardno područje zakivanja

Prednosti

Visoki kvalitet zakovanih spojeva.

- Čist i čvrst formirani spoj.
- Pouzdano, patentirano završljiva-nje trna zakovice.
- Konstantno visoka jačina na isteza-nje i smicanje.
- Visoka jačina zakovanih spojeva, otpornih na udare i prskajuću vodu.
- Bez izvijanja čahure zakovice kod malih nominalnih područja stezanja.

d x l mm	Prečnik otvora Ø mm	Štežno područje mm	d _k mm	k mm	Sila kidanja smicanjem N	Sila kidanja istezanjem N	Art.-Nr.	Pak/kom
3,0 x 6,0	3,1	1,5 - 3,5	6,4	1,1	550	820	2936 3 6C	500
3,0 x 8,0	3,1	3,5 - 5,5	6,4	1,1			2936 3 8C	500
3,0 x 10,0	3,1	5,5 - 7,0	6,4	1,1			2936 3 10C	500
3,0 x 12,0	3,1	7,0 - 9,0	6,4	1,1			2936 3 12C	500
3,2 x 6,0	3,3	0,5 - 3,5	6,4	1,1	750	1000	2936 32 6C	500
3,2 x 8,0	3,3	0,5 - 3,5	6,4	1,1			2936 32 8C	500
3,2 x 10,0	3,3	5,5 - 7,5	6,4	1,1			2936 32 10C	500
4,0 x 6,0	4,1	0,5 - 3,5	8,0	1,4	1200	1750	2936 4 6C	500
4,0 x 8,0	4,1	3,0 - 5,0	8,0	1,4			2936 4 8C	500
4,0 x 10,0	4,1	5,0 - 6,5	8,0	1,4			2936 4 10C	500
4,0 x 12,0	4,1	6,5 - 8,5	8,0	1,4			2936 4 12C	500
4,0 x 16,0	4,1	8,5 - 12,5	8,0	1,4			2936 4 16C	500
4,0 x 20,0	4,1	12,5 - 16,5	8,0	1,4			2936 4 20C	500
4,8 x 8,0	4,9	3,0 - 4,5	9,6	1,6	1600	2200	2936 48 8C	500
4,8 x 10,0	4,9	4,5 - 6,0	9,6	1,6			2936 48 10C	500
4,8 x 16,0	4,9	6,0 - 12,0	9,6	1,6			2936 48 16C	250
5,0 x 10,0	5,1	4,5 - 6,0	9,6	1,6	1650	2700	2936 5 10C	500
5,0 x 12,0	5,1	6,0 - 8,0	9,6	1,6			2936 5 12C	250
5,0 x 16,0	5,1	8,0 - 12,0	9,6	1,6			2936 5 16C	500
5,0 x 20,0	5,1	12,0 - 16,0	9,6	1,6			2936 5 20C	250
5,0 x 25,0	5,1	16,0 - 21,0	9,6	1,6			2936 5 25C	250

