



Slijepa zakovica

Zaobljena glava sa ravnim dosjedom

Čahura zakovice: čelik pocinčani, plavo pasivirani
Trn zakovice: čelik pocinčani, plavo pasivirani

d x l mm	Prečnik otvora Ø mm	Područje stezanja mm	d _k mm	k mm	Sila kidanja smicanjem N	Sila kidanja istezanjem N	Art.-Nr.	Pak/ kom
3,0 x 6,0	3,1	0,5 – 3,0	6,5	0,8	1100	1200	2935 3 6C	500
3,0 x 8,0	3,1	3,0 – 5,0	6,5	0,8	1100	1200	2935 3 8C	500
3,0 x 10,0	3,1	5,0 – 7,0	6,5	0,8	1100	1200	2935 3 10C	500
3,2 x 6,0	3,3	0,5 – 3,5	6,5	0,8	1300	1500	2935 32 6C	500
3,2 x 8,0	3,3	3,5 – 5,0	6,5	0,8	1300	1500	2935 32 8C	500
3,2 x 10,0	3,3	5,0 – 7,0	6,5	0,8	1300	1500	2935 32 10C	500
3,2 x 12,0	3,3	7,0 – 9,0	6,5	0,8	1300	1500	2935 32 12C	500
4,0 x 8,0	4,1	2,5 – 4,5	8,0	1,0	2000	2300	2935 4 8C	500
4,0 x 10,0	4,1	4,5 – 6,5	8,0	1,0	2000	2300	2935 4 10C	500
4,0 x 12,0	4,1	6,5 – 8,5	8,0	1,0	2000	2300	2935 4 12C	500
4,0 x 16,0	4,1	8,5 – 12,5	8,0	1,0	2000	2300	2935 4 16C	500
5,0 x 10,0	5,1	4,0 – 6,0	9,5	1,1	3400	4000	2935 5 10C	500
5,0 x 12,0	5,1	6,0 – 8,0	9,5	1,1	3400	4000	2935 5 12C	500
5,0 x 16,0	5,1	8,0 – 11,0	9,5	1,1	3400	4000	2935 5 16C	500

