

Fix anker C-Line

Čelik pocinčani, žuto kromirani

Područje primjene:

- Univerzalna tipla za pričvršćivanje u zoni pritiska.
- Upotreblijiva u betonu B 25 i u prirodnom kamenu.
- Namijenjen za pričvršćivanje metalnih konstrukcija, metalnih profila, podnožja, konzola, ograda, rešetaka, mašina, drvenih konstrukcija, kratkih željeznih klinova, podrožnjača, oslonaca, kablovskih kanalicā.




Tehnički podaci

Art.-Nr.	Opis	M* x L* mm	L1* mm	D1* mm	D2* mm	Pak/ kom
2904 16 30C	TIPLA ANKER ZN/ŽCR M6/30/70	M6 X 70	25	35	30	100
2904 16 55C	TIPLA ANKER ZN/ŽCR M6/55/95	M6 X 95	25	35	55	100
2904 18 35C	TIPLA ANKER ZN/ŽCR M8/35/80	M8 X 80	25	40	35	100
2904 18 50C	TIPLA ANKER ZN/ŽCR M8//50/95	M8 X 95	25	40	50	100
2904 18 75C	TIPLA ANKER ZN/ŽCR M8/75/120	M8 X 120	25	40	75	100
2904 11020C	TIPLA ANKER ZN/ŽCR M10/20/80	M10 X 80	30	50	20	50
2904 11035C	TIPLA ANKER ZN/ŽCR M10/35/95	M10 X 95	30	50	35	50
2904 11055C	TIPLA ANKER ZN/ŽCR M10//55/115	M10 X 115	30	50	55	50
2904 11070C	TIPLA ANKER ZN/ŽCR M10/70/130	M10 X 130	30	50	70	50
2904 11220C	TIPLA ANKER ZN/ŽCR M12/20/80	M12 X 80	40	60	20	50
2904 11230C	TIPLA ANKER ZN/ŽCR M12/30/100	M12 X 100	40	60	30	25
2904 11250C	TIPLA ANKER ZN/ŽCR M12/50/120	M12 X 120	40	60	50	25
2904 11265C	TIPLA ANKER ZN/ŽCR M12/65/135	M12 X 135	40	60	65	25
2904 11615C	TIPLA ANKER ZN/ŽCR M16/15/105	M16 X 105	60	70	15	20
2904 11640C	TIPLA ANKER ZN/ŽCR M16/40/140	M16 X 140	60	80	40	20

M* - Navoj vijka
L* - Ukupna dužina tiplē
L1* - Dužina navoja
D1* - Minimalna dubina postavljanja
D2* - Maksimalna visina ugradbenog elementa


Uputstvo za postavljanje




Izbušiti rupu



Očistiti rupu



Postaviti anker
zakucavanjem



Zavrnuti sa moment
ključem