

MIG 350 SYN

2 postupka zavarivanja sa jednim aparatom:
MIG/MAG i REL postupak
Half-synergic (poluautomatska) kontrola parametara
350 A



MIG 500 SYN

2 postupka zavarivanja sa jednim aparatom:
MIG/MAG i REL postupak
Half-synergic (poluautomatska) kontrola parametara
Vodeno hlađenje gorionika za sigurniji i duži rad
500 A



MIG 500 SYN pulse

4 postupka zavarivanja sa jednim aparatom:
MIG/MAG, PULSNI MIG, DUPLI-PULS MIG, REL
Full-synergic (full - automatska) kontrola parametara
Vodeno hlađenje gorionika za sigurniji i duži rad
500 A



MIG 350 SYN	MIG 500 SYN	MIG 500 SYN pulse
40-350 A	40-500 A	30-500 A
40-350 A	40-490 A	10-500 A
-	-	-
Ø200-300 mm/5-15-20 kg	Ø200-300 mm/5-15-20 kg	Ø200-300 mm/5-15-20 kg
Ø0,8-1,2 mm	Ø0,8-1,6 mm	Ø0,8-1,6 mm
Ø0,8-1,2 mm	Ø0,8-1,6 mm	Ø0,8-1,6 mm
Max. Ø6 mm	Max. Ø8 mm	Max. Ø8 mm
-	-	-
60%	60%	80%
400 V, trofazni	400 V, trofazni	400 V, trofazni
20 A	35 A	55 A
576x297x557 mm	1100x510x1000 mm	1133x498x1508 mm
60 kg	127,5 kg	112 kg